




Fixture Type  
Materials  
Finish

Table  
Aluminum & Glass  
Anthracite

Lamp Type  
Lamp Quantity  
Lamp Included  
Wattage  
Input Voltage  
Delivered Lumens  
Kelvin  
CRI  
Power S Type  
Power S Quantity  
Power S Location  
Dimming Type

LED  
1  
Yes  
2.5 W  
5 VAC  
115 lm  
2700 K  
90  
Driver  
1  
Integrated  
4-Step Dimming



Designer

FLOS

Listings

CE  
WET

Note: this product is not UL certified.  
We offer UL certification for an  
additional cost and lead time.



Portable version equipped with a carrying handle. Adjustable driver 5/100=240V/50-60Hz integrated in the body of the luminaire with optical switch sensor on the head and with a 4-step dimming function: 100%-50%-3%-OFF. Rechargeable with a 120cm long Micro USB-C cable ensuring continuous emission for up to 6 hours. Charger with interchangeable EUR, UK and USA plugs.



## Main specifications

Mounting	Table
Environments	Outdoor wet location
LED type	Edge Lighting
Lamp category	LED
Power (W)	2.5W
Source flux (lm)	182
System flux (lm)	115

## Physical

Colour	Anthracite
Trim	No
Orientation	Fixed
Net weight (kg)	1
IP internal	65

## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
Beam angle C0-180 (°)	106
Beam angle C90-270 (°)	106

## Electrical

Insulation class	III
Frequency (Hz)	50-60
Main voltage (Vac)	5/100=240V
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmer on board
Emergency type	No

